

## 8-015 / Connecting Link

### Grade 80 Lifting Chain & Fittings

New



#### Description

★Design factor 4:1 proof tested and certified. Tested acc. to DIN EN 1677


#### Remark

Code " YA "



## Specification

Item No.	Working Load Limit	For Grade 80 Chain(mm)	Dimensions (mm)				N.W
			A	B	D	K	
	tonnes*	mm					Kg
8-015-05	0.8	5	10	13	6	35	0.0
8-015-06	1.12	6	15	17	7	44	0.0
8-015-07	2.0	7, 8	18	22	9	57	0.2
8-015-10	3.15	10	25	26	11	68	0.3
8-015-13	5.3	13	30	35	16	91	0.7
8-015-16	8.0	16	36	38	19	100	1.1
8-015-20	12.5	18, 20	42	46	22	122	1.9
8-015-22	15.0	22	49	59	24	152	3.0
8-015-26	21.2	26	55	62	30	162	5.0
8-015-32	31.5	32	69	79	36	202	9.0



- Quenched and Tempered Alloy Steel.
- At least 25% greater WLL than traditional G80 products.
- Manufactured in accordance with EN 1677- 1 and ASTM A952/ A952M, DIN PAS 1061.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Design Factor 4:1.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Suitable for use with both Grade 80 and Grade 100 chain.



Repair kit available for maintenance.

## G-100 Connecting Link

Item No.	For Grade 100 Chain	WLL tonnes*	Dimensions (mm)				N.W. kg
	mm		A	B	D	K	
X-015-06	6	1.4	15	18	7	45	0.08
X-015-07	7, 8	2.5	18	25	9	59	0.2
X-015-10	10	4.0	25	28	11	69	0.3
X-015-13	13	6.7	30	38	16	92	0.7
X-015-16	16	10.0	36	41	19	101	1.2
X-015-20	20	16.0	42	50	23	122	2.1
X-015-22	22	19.0	49	63	24	152	3.5
X-015-26	26	26.5	55	66	30	162	4.8
X-015-32	32	40.0	69	85	36	203	9.0

★ Design factor 4:1 proof tested and certified.